

**CAUTION
KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING**

LANOLUBE

**Liquid Lanolin Anti-Corrosive Lubricant
and Protective Coating**

Active Constituents :

Lanolin

Petroleum Solvent

580g/L

**LUBRICANT
CORROSION INHIBITOR
WATERPROOFING AGENT
ACID & SALT RESISTANT
NON-EVAPORATIVE
NON-CONDUCTIVE**



5 LITRES

HAZARD CLASSES 3.1D, 6.1E, 6.3B, 9.1B HSR002602
COMBUSTIBLE LIQUID: Flash Point 66°C, TOXIC, ECOTOXIC

WARNING: Harmful if swallowed. May cause irritation to eyes and skin. Do not breath vapour.

ENVIRONMENTAL WARNING: Toxic to aquatic organisms. Avoid contaminating waterways. Readily biodegradable.

PRODUCT DISPOSAL: Do not allow product to enter waterways, drains or sewers. Absorb spillage on inert material such as soil and dispose of in a suitable landfill.

CONTAINER DISPOSAL: Triple rinse container and return to recycler. Alternatively, ensure container is completely empty, burn if permitted and circumstances, especially wind direction allow, otherwise bury in landfill.

HANDLING PRECAUTIONS: When mixing or applying wear protective clothing, goggles or face shield and respirator if risk of inhalation. Do not eat or drink while using. Wash hands and face before meals and after work. Wash protective clothing after work.

STORAGE: Store in original container tightly closed and in dry, cool, well ventilated area, away from foodstuffs.

FIRST AID: If swallowed DO NOT induce vomiting. Rinse mouth with water and give water to drink. **For advice, have product container or label at hand** and contact the **National Poisons Centre 0800 POISON (0800 764 766)** or a doctor immediately. If skin, hair or eye contact occurs, remove contaminated clothing and flush skin, hair and/or eyes with running water for several minutes. Additional information is contained in the **Material Safety Data Sheet** which is available from the reseller at point of purchase or visit www.sstaustalia.com for alternate contact details. **In Australia, phone 13 11 26.**

CAUTION: Allow solvent to evaporate before applying voltage or flame (minimum 1-2 hours subject to ambient temperature).

Directions for use

AGRICULTURE

Corrosion protection of fertilizer spreaders, spraying equipment, stock crates, headers, air seeder boxes, tractors, chains and tools. Lubrication of drench guns, gates, cattle crushes, nuts, bolts and tools. Release agent for soil corers.

AUTOMOTIVE

Rust proofing, moisture dispersant for ignition systems, battery terminal corrosion protection and thread anti-seize. Not suitable for high speed bearings.

MARINE

Lubrication and waterproofing of switches and components, corrosion protection and lubrication of all moving metal parts and resists water washout.

INDUSTRIAL / BUILDING

Reduce welding spatter adhesion, corrosion protection and lubrication of machinery, tools and chains. Release agent for concrete formwork. Protective coating for timber decks and fences.

HOUSEHOLD

Lubrication and corrosion protection of sporting weaponry, door locks, fishing and camping equipment, boats, trailers and lawn mower cutting decks. Waterproofing of canvas, leather and outdoor furniture.

GENERAL INSTRUCTIONS

Shake container well before each use. Spray Lanolube onto a clean dry surface. Allow solvent carrier to evaporate before use.

CONDITIONS OF SALE: The use of Lanolube being beyond the control of the manufacturer, no warranty expressed or implied is given by SST Australia Pty Ltd. regarding its suitability, fitness or efficiency for any purpose for which it is used by the buyer, whether in accordance with the directions or not and SST Australia Pty Ltd accepts no responsibility for any consequences whatsoever resulting from the use of this product.

Batch No.
D.O.M

In an Emergency
Dial 000 Police or Fire Brigade
Poisons Information Centre (Ph 13 11 26)

NZ EMERGENCY PHONE NUMBER IS
NATIONAL POISONS CENTRE
0800 POISON (0800 764 766)

SST Australia Pty Ltd 70 Quantum Close, Dandenong South, VIC, 3175 ph : +61 9720 6306

